

REPLACEMENT PARTS GUIDE

5E-900 Tractor (China Edition)

ENGINE



OIL FILTER

[RE504836](#)

Replace after every 500 hours.
(If not using PLUS-50 oil and John Deere Filter, this service interval should be shortened to 250 hours.)



FUEL FILTER

PRIMARY

[RE509208](#)



FINAL

[RE526557](#)

Replace after every 500 hours.



PRIMARY AIR FILTER

[AL172780](#) (300001 -)

[RE253519](#) (- 300000)

SECONDARY AIR FILTER

[AL150288](#) (300001 -)

[RE253518](#) (- 300000)

Service as required.



HYDRAULIC



HYDRAULIC FILTER

[RE45864](#)

Replace after first 100 hours then after every 500 hours.



JOHN DEERE

Genuine Parts and Service

CAPACITIES

5E-900 Tractor (China Edition)

CAPACITIES (Approximate):

Fuel Tank:

..... 120 L (32 gal)

**Cooling System:
Cool-Gard™ II**

..... 13.5 L (3.56 gal)

**Crankcase with Filter:
Plus-50™ II**

..... 15 L (3.96 gal)

**Transmission and Hydraulic System:
Hy-Gard™**

..... 39 L (10.30 gal)

[Return to Filter Overview](#)

REPLACEMENT PARTS GUIDE

5E-900 Tractor (China Edition)

ENGINE



BRAKE DISK
[SJ17870](#)



CLUTCH DISK
[RE225677](#) (Traction)
[SJ23134](#) (PTO)



ALTERNATOR
[SJ24309](#) (90A)
[SJ21631](#) (75A)



BATTERY
[SJ19484](#)



FAN BELT DRIVE
[SU38021](#) (W/O A/C, W/O AP)
[SU38053](#) (Fan Drive)



CAB



SEAT
[SJ20422](#) (W/ Armrest)
[SJ17864](#) (OOS)
[SJ29370](#) (Bottom)
[SJ29371](#) (Back)



JOHN DEERE
Genuine Parts and Service

CLICK PART NUMBER TO BUY

*See operator's manual for additional details.